

*6/91* 

WH 6 / WH 9 PRO

portable

## cartridge operated

# water

#### GLORIA WH 6 / WH 9 PRO – strike-knob, cartridge operated water extinguishers

A comprehensive product range with consistent strike-knob operation, with an in-house developed, fibre-glass reinforced, high-quality special plastic valve in the distinctive GLORIA design, integrated with stable handle for easy carrying.

GLORIA water WH PRO extinguishers can be used in the following fire classes:

Туре	Α	В	С	MED
WH 6 PRO	34	-	-	=
WH 9 PRO	43	-		=2

#### Areas of use:

- Agricultural sector
- File storage
- Offices
- Wood processing
- · Paper and Packaging storages
- Textiles
- Firing ranges and banquettes
- Marine industry
- Living areas

Extinguishing agent definitely without environmentally damaging, perfluorinated tensides PFOS or PFOA

Extinguishers leave minimum contamination after the fire fighting deployment.

Water extinguishers with a capacity of 6 and 9 l of water, enriched only with a biodegradable, impregnating additive.

Hose connection and diptube made o stainless steel Extinguishers with special nozzle for high area protection and

With colour coding of extinguishing agent - the blue colour code

Serially equipped with quality wall bracket, appropriate car brackets are available separately.



# GLORIA PRO line - environmentally friendly water extinguisher with top level results - 9 litre with 43 A!

GLORIA WH PRO series - fire extinguishers with rating up to 43 A – without additives harmful to the environment. Water extinguishers comparable to foam fire extinguishers in the A-rating.

Especially useful in extinguishing of wood, paper and textile, due to good wetting of hydrophobic materials.



### WH 6 / WH 9 PRO

# portable



- Pull the yellow safety pin (△).
- By operating the strike knob
  ⑤, the puncture pin ⑥ laps
  the CO<sub>2</sub> gas cartridge ⑥.
- Abruptly CO<sub>2</sub> flows into the container.
- Through the diptube the extinguishing agent gets into the hose assembly .
- The rotating and suppressible extinguishing pistol 6 allows for a targeted and largescale fire fighting.





## cartridge operated

# Product and performance features

- Fire extinguisher container with two suspension clips, made from high quality steel, externally covered with hard-wearing polyester resin powder coating, free from heavy metals.
- Wet fire extinguishers with high-quality, long-lasting internal coating against corrosion.
- Consistent, high-strength fibre-glass reinforced special plastic valve body – strong, sturdy, stable, moisture resistant, corrosion free, high temperature resistant, LIV resistant
- Large, maintenance friendly neck ring M 74, consistent, black-coloured, anodi sed metal union nut.
- Internal CO<sub>2</sub>-gas cartridge with PE-co ating and connection thread M 18
- Shock-resistant plastic footring ensuring stability and protection against damages and corrosion.
- Three bolts welded on the bottom of the container ensure excellent fitting of the footring against drop-off or twisting.
- Long-lasting hose assembly with fabric lining made from synthetical rubber material.
- Approved to use on electrical installations up to 1000 V at minimum distance 1 m
- Each fire extinguisher delivered in a separate cardboard box.



Туре	Model	PN	Weight of charge unit [kg]	Extinguishing agent	Oty of extinguishing agent [[]	Propellant gas	Discharge time [s]	Throw [m]	Working temperature [°C]	Bracket H.W/D, Ø [mm]
WH 6 PRO	W6H	803801.0000	≈10,3	Water with impregnate	6	CO2	64	4	0 / +60	555 / 280 / 165, 150
WH 9 PRO	W9H	803811.0000	≈16,5	Water with impregnate	9	CO <sub>2</sub>	93	4	0 / +60	585 / 280 / 205, 190

GLORIA WH 6 / WH 9 PRO - technical data.

"Subject to technical changes

