S 2 LW

portable

foam

GLORIA S 2 LW – handy stored pressure equipment, with film-forming agent

Fire hazards can never be eliminated completely. The fire risk can be reduced though. With a fire extinguisher most fires could already be fought successfully at the very beginning. Protect Your family, home and property with a GLORIA fire extinguisher.

GLORIA fire extinguishers S 2 LW can be used in the following fire classes:

Туре	А	В	С	MED	
S 2 LW with fire blanket	5	70	_	122	
S 2 LW	5	70	-	-	

Areas of use:

- Living spaces
- Workrooms
- Ironing rooms
- Kitchens
- Firesides
- RVs and caravans
- Sailing and motor boats
- Weekend and summer houses

High performance, film-forming extin-

Contrary to powder, it does not cause a "dust cloud" effect which may impede breathing and sight. Indisputable advantage is ease and cheap cleaning afterwards.

Ergonomic and intuitive design of fire extinguishers - allows easy handling in emergencies.

Minimized external dimensions thanks to special valve and container construction. Equipped with stable wall bracket and strang in standard

S 2 LW with 1 x 1 m fire blanket in Fire--Box set - coverlet is easy removable, and perfectly protected against dirt

High extinguishing power and extremely long duration of extinguishing stream



GLORIA S 2 LW - designed for one handed operation, simultaneously to carry and trigger

Large handle allows secure handling operation (bearing, aiming and triggering by one hand) in every situation. Rounded edges as specified by the automotive industry.

Sturdy handle with clearly marked operating elements:

- 1 Securing key (yellow),
- 2 Extinguishing key (white).

21

stored pressure

S 2 LW

portable



- Push the **yellow button** ♠ extinguisher is ready to use.
- Push the white button (B) the valve (O) opens.
- Extinguishing agent enters the diptube from where it goes to the nozzle .







Product and performance features

- Fire extinguisher container made from aluminium, with high quality powder coating (free of environmentally-damaging substances, like cadmium, TGIC) guarantees long life of extinguisher.
- Special Internal polythene durable synthetic coating.
- High strength brass valve body strong, sturdy, stable, with spraying nozzle.
- Valve case made of special durable plastic.
- Operational readiness easy to visual inspection at any time through integrated manometer.
- Backflashes are limited to the greatest possible extent.
- Suspendable stream of extinguishing agent depending on the situation.
- S 2 LW with fire blanket fire blanket used also to suppress fires of deep fryers containing up to 3 kg of fat, fire blanket material - fibreglass fabric with silicone-coating.
- Legible marking of extinguisher according to standard EN 3-7 with a permanent screen printing technique.
- Each fire extinguisher delivered in a separate cardboard box
- Approved to use on electical installations up to 1000 V at minimum distance 1 m.
- Possible MED certification on demand.

Туре	Model	PN	Weight of char- ge unit [kg]	Extinguishing agent	Oty of exting agent [kg]	Propellant gas	Discharge time [s]	Throw [m]	Working temperature [°C]	Bracket H/W/D, Ø [mm]
S 2 LW with fire blanket	S2L	002536.2042	≈4,3	AB Foam	1	nitrogen	25	4	0/+60	370*/230*/160*, 108
S 2 LW	S2L	001551.0000	≈3,1	AB Foam	1	nitrogen	25	4	0/+60	365 / 152 / 110, 108

GLORIA S 2 LW - technical data, * - dimensions of Fire-Box

"Subject to technical changes



GS (CERT

PHONE +48 17 22 10 206 FAX +48 17 22 10 241 pfx@fs.utc.com

