

*50 l* 

**SDE 50** 

wheeled

### stored pressure

### foam

#### GLORIA SDE 50 - designed to use by one person, wheeled stored pressure foam extinguisher

The perfect supplement for facilities with high fire hazard, particularly suitable for liquid fires.

GLORIA wheeled foam extinguisher may be used in the following fire classes:

| Туре          | А | В    | C | D | MED |
|---------------|---|------|---|---|-----|
| SDE 50 /5 /10 | • | IV B | - | - | 0   |

#### Areas of use:

- Storages with synthetical material
- Airports
- Fuel depots
- Chemical industry
- Large car parks
- Areas with burning liquids

The specially designed ergonomic extinguishing device with patented foam nozzle ensures a steady flow of foam with a very low drop in pressure. Swivel coupling allows easy unroling of the hose avoiding twisting.

Detachable frame with no welding on the cylinder, which ensure better and higher safety.

Also more convenien when there is a need for transportation.

Approved acc. to EN

Application only in voltage-free systems



# **GLORIA SDE 50 - immediately ready for use thanks to permanent pressure construction!**

Foam units, for large areas threatened by potentially rapid spread of fire.

An extinguishing agent forming a film with long time of foam layer coverage on burning material.

Particularly suitable for locations with increased risk of liquid substances ignition.

## *50 I*

### stored pressure

### **SDE 50**





- Remove the safety pin (4).
- Open valve <sup>(3)</sup> with lever <sup>(4)</sup>.
- The foam streams through a siphon tube ① into the hose assembly ②.
- The rotating and suppressible extinguishing device allows for a targeted fire fighting.







## Product and performance features

- Extinguishing agent container entirely made of stainless steel, externally coated with weather-proof and durable coating (free from heavy metals) for a long life-time.
- Valve made of brass, with pressure gauge, PRV (Pressure Release Valve) and green safety seal for constant visual inspection. Only a simple glance is enough to check if the extinguisher has been tampered.
- Durable hose assembly with fabric lining made from synthetical rubber material (EPDM). Resistant to bending and space-saving thanks to placement of hose around the extinguisher cylinder.
- Large steel wheels (30 cm) with solid rubber tires - convenient use by one person.
- Tilt-proof with ideal center of gravity.
- Stable support thanks to safe stand.
- Legible and informative multi-language label.



|        | Model    | PN                                    | Weight<br>of charge unit [kg] | Extinguishing agent    | City of extinguishing<br>agent [kg] | Propellant<br>gas | Discharge<br>time [s] | Throw [m] | Working<br>temperature [°C] | Bracket H/W/D, Ø [mm] |
|--------|----------|---------------------------------------|-------------------------------|------------------------|-------------------------------------|-------------------|-----------------------|-----------|-----------------------------|-----------------------|
| SDE 50 | S 50 L-0 | 5 m: 000870.2851<br>10 m: 000871.2851 | ≈ 80                          | Foam concentrate+water | 50                                  | Nitrogen          | 47                    | 10        | 0/+60                       | 1150 / 490 / 580, 315 |

GLORIA SDE 50 - technical data

subject to technical changes

